UNILUMIN UPAD IV-S 1.9 PRODUCT OVERVIEW

SPECIFICATION

1.9mm LED Videowall Solution 🔻

The Unilumin UPAD IV-S 1.9 is an LED videowall solution that features a versatile curvable unit that can be used to create tight curves and unique arrangements that no other panel can accomplish.

INGRESS PROTECTION		IP 4
OPTIMAL VIEW DISTANCE		1.9m
PIXEL PITCH		1.9mm
MAXIMUM PANEL CURVE		+40° / -40 °
RESOLUTION		256рх х 256рх
WEIGHT		7.7 KG
POWER DRAW		45 W
DIMENSIONS	500mm x 500mm x 80mm	

USE CASES

WAVE 🔻

By combining 2 or more panels and inverting the curves as they are built, a wave formation can be created.

CIRCLE 🔻

A circle can be achieved with 9 panels and can be stacked to create totems and flying arrangements

TIGHT CURVE 🔻


The UPAD IV-S panels can curve up to 40 degrees, meaning a tight curve can be achieved with minimal panels








CABINET DIMENSIONS














Want to know more about our **Unilumin UPAD IV-S?** Visit our online catalogue at <u>dbpixelhouse.com/hire</u>



All measurements are in millimetres (mm) | This spec-sheet utilises rendered graphics which are illustrative and not 100% accurate